


SPECIFICATION

- (1) ITEM NO. : BH-321-2DL
- (2) WITH LONG SOLDER LUG, BRASS NICKEL PLATED
- (3) HOLDER MATERIAL: PP 94HB RESIN, BLACK COLOR
- (4) SPRING MATERIAL: $\text{Ø}0.65$ MM SPRING STEEL NICKEL PLATED
- (5) RIVET MATERIAL: BRASS NICKEL PLATED
- (6) RoHS COMPLIANT

△	Changed P.P.D.configuration	AUG03/2012		
△	1. Changed P.P.D.dimension from 1.7 to 2.2 2. Changed the positive rivet from 5x2.4x4 to 8x2.4x4	FEB/14/2012		
△	Changed P.P.D.dimension from 1.4 to 1.7, from 2.2 to 3.17	NOV/16/2011		
△	Changed P.P.D.dimension from 2.0 to 1.4	JUL/03/2004		
NO.	MODIFICATION	DATE	SCALE	1:1
General Tolerances			UNIT	MM
0 ~ >3	± 0.10	30 ~ >120	± 0.30	 The Third Angle Projection
3 ~ >6	± 0.10	120 ~ >400	± 0.50	
6 ~ >30	± 0.20	Angle: $\pm 3^\circ$		
			MAT'L	SEE SPEC.
			DATE	DEC. 25. 2002

SHOGYO INTERNATIONAL CORP.
BH-321-2D
 BATTERY HOLDER