



SPECIFICATION

- (1) ITEM NO. : BH-331-3A
- (2) WIRE: UL1007 AWG#26
BLACK & RED $150\text{MM} \pm 5\text{MM}$
STRIP & TIN $5\text{MM} \pm 1\text{MM}$
- (3) HOLDER MATERIAL: P. P. RESIN, BLACK COLOR
- (4) SPRING MATERIAL: $\text{Ø}0.7$ MM 65C SPRING STEEL NICKEL PLATED
- (5) RIVET MATERIAL: BRASS NICKEL PLATED
- (6) RoHS COMPLIANT

3		
2		
1		

NO.	MODIFICATION	DATE	SCALE	1:1	APPD	<i>[Signature]</i>	
General Tolerances			UNIT	MM	CHKD	<i>[Signature]</i>	
0 ~ >3	± 0.10	30 ~ >120	± 0.30	MAT'L	SEE SPEC.	DWN	CHENGZHENHUA
3 ~ >6	± 0.10	120 ~ >400	± 0.50	DATE	JUL. 22. 2011	DR NO	3313A-0711
6 ~ >30	± 0.20	Angle: $\pm 3^\circ$	The Third Angle Projection				

SHOGYO INTERNATIONAL CORP.

BH-331-3A

BATTERY HOLDER