


PCB MOUNTING LAYOUT

NOTES:

1. MATERIAL:
HOUSING: PBT UL94V0 BLACK COLOR
CONTACT: STAINLESS STEEL #301, 0.15MM THK
TIN PLATED OVER NICKEL
2. CURRENT RATING : 3A (AC/DC)
3. VOLTAGE RATING : 500V (AC/DC)
4. CONTACT RESISTANCE: 100 MILLIOHMS
5. INSULATION RESISTANCE: 100 MEGAOHMS
6. TEMPERATURE RANGE: -55°C TO +85°C
7. HUMIDITY: 40°C AND 90-95% RH FOR 96 HOURS
8. RoHS COMPLIANT

| 3 | | | | |
|---|--------------|------|-------|---------------|
| 2 | | | | |
| 1 | | | | |
| NO. | MODIFICATION | DATE | SCALE | 2:1 |
|  | | | UNIT | MM |
| General Tolerance Dim: 0.0 ±0.30 0.30 ±0.20 Angle: ±3° 0.000 ±0.10 | | | MAT'L | AS NOTES |
| | | | DATE | MAR. 25. 2008 |

| |
|-----------------------------------|
| SHOGYO INTERNATIONAL CORP. |
| #CH004-2032LF |
| COIN CELL HOLDER |