



Breakdown voltage: 500VAC for one minute  
 Insulation resistance: 100MΩ min. at 500VDC  
 Contact resistance: 50mΩ Max.

14	CABLE PROTECTOR	1	POLY VINYL CHLORIDE	
13	CAP	1	BRASS	Ni-PLATED
12	TERMINAL C	1	STEEL	Ni-PLATED
11	INSULATOR C	1	POLYVINYL CHLORIDE	
10	TERMINAL B	1	BRASS	Ni-PLATED
9	TERMINAL A	1	STEEL	Ni-PLATED
8	INSULATOR B	1	A.B.S. RESIN	
7	BODY	1	A.B.S. RESIN	
6	PIN	1	STEEL	Ni-PLATED
5	SLEEVE	1	BRASS	
4	CONTACT C	1	BRASS	Ni-PLATED
3	CONTACT B	1	BRASS	Ni-PLATED
2	INSULATOR A	1	A.B.S. RESIN	
1	CONTACT A	1	BRASS	Ni-PLATED
LET	PART NAME	QTE	MATERIAL	REMARK
DRAWN	S.T	SCALE	2/1	
CKD		3RD ANGLE PROJ		
APPR		DATE	SEP. 30 1989	

TOLERANCE ±0.3mm

**SHOGYO INTERNATIONAL CORP.**  
**# MP-120MS**