



Pin Hole Layout  
(Jack Bottom View)

NO.	Description	Material	Q'TY	Finish
6.	Cover	PBT+30%G	1	Black Color
5.	Housing	PBT+30%G	1	Black Color
4.	Pin(2.0 $\phi$ )	Copper	1	Nickel Plated
3.	Break Terminal	0.4T Brass	1	Silver Plated
2.	Sleeve Spring	0.2T Phosphor Bronze	1	Silver Plated
1.	Pin Terminal	0.4T Brass	1	Silver Plated

RoHS  
Compliant

For Reference  
僅供參考

SPECIFICATIONS:

Contact Resistance : 30m $\Omega$  max  
 Current Rating : Max 5.0A , 24V DC  
 Insulation Resistance : 100M $\Omega$  min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark:  $\blacktriangle$ : The Most Important Dimension

DATE	DWN	CHKD	APVD	MANAGER
11.05.2012				

PART NAME : DC POWER JACK	VERSION:7.0
TOLERANCE : $\pm 0.3$ mm UNLESS OTHERWISE SPECIFIED	UNIT:mm   SCALE:

**SHOGYO INTERNATIONAL CORP.**

**#SCD443CCS011B00G**