



| 5. | Housing | ABS | 1 | Black Color |
|-----|-----------------|----------|------|---------------|
| 4. | Ground Terminal | Brass | 1 | Nickel Plated |
| 3. | Outer Sleeve | Brass | 1 | Nickel Plated |
| 2. | Inner Barrel | Brass | 1 | Nickel Plated |
| 1. | Insulator Ring | POM | 1 | Black Color |
| NO. | Description | Material | Q'TY | Finish |

| DATE | DWN | CHKD | APVD | MANAGER |
|------------|-----|------|------|---------|
| 10.15.2008 | | | | |

PART NAME: 2.5φ DC PLUG

VERSION: 4.0

TOLERANCE: 0>1.0=±0.1 1.0>6.0=±0.2 6.0>12.0=±0.3
12.0>25.0=±0.4 25.0>=±0.5

UNIT:mm



SCALE: 1/1

SPECIFICATIONS:

Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min.at DC500V
 Dielectric Withstand Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

RoHS
Compliant

For Reference
僅供參考

SHOGYO INTERNATIONAL CORP.

SCDP601PTN00000G

DC Power Plug