



Pin Hole Layout
(Jack Bottom View)

NO.	Description	Material	Q'TY	Finish
11.	Cover	POM	1	White Color
10.	Housing	PBT	1	Black Color
9.	Make Terminal	0.20T Phosphor Bronze	1	Silver Plated
8.	Separator Spring	0.25T Phosphor Bronze	1	Silver Plated
7.	Break Terminal	0.30T Brass	1	Silver Plated
6.	Make Terminal	0.20T Phosphor Bronze	1	Silver Plated
5.	Separator Spring	0.25T Phosphor Bronze	1	Silver Plated
4.	Break Terminal	0.3T Brass	1	Silver Plated
3.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Tip Spring	0.3T Phosphor Bronze	1	Silver Plated
1.	Earth Spring	0.2T Phosphor Bronze	1	Silver Plated

DATE	DWN	CHKD
01.16.2012		

SPECIFICATIONS:

Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most important Dimension

RoHS
Compliant

SHOGYO INTERNATIONAL CORP.

SCJ348P00(*)S0B00G

PART NAME : 3.5 ϕ PHONE JACK

TOLERANCE : ± 0.3 mm UNLESS OTHERWISE SPECIFIED

UNIT:mm