



Pin Hole Layout  
(Jack Bottom View)

| 9.  | Spring           | SUS-304               | 1    |               |
|-----|------------------|-----------------------|------|---------------|
| 8.  | Cover            | PC                    | 1    | Trans Parent  |
| 7.  | Housing          | POM                   | 1    | Black Color   |
| 6.  | Barrel(W/Thread) | Brass                 | 1    | Nickel plated |
| 5.  | Tip Spring       | 0.25T Phosphor Bronze | 1    | Silver Plated |
| 4.  | Break Terminal   | 0.4T Brass            | 1    | Silver Plated |
| 3.  | Break Terminal   | 0.4T Brass            | 1    | Silver Plated |
| 2.  | Ring Spring      | 0.25T Phosphor Bronze | 1    | Silver Plated |
| 1.  | Earth Terminal   | 0.4T Brass            | 1    | Silver Plated |
| NO. | Description      | Material              | Q'TY | Finish        |

|            |     |      |
|------------|-----|------|
| DATE       | DWN | CHKD |
| 10.10.2011 |     |      |

PART NAME :3.5φ PHONE JACK

TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm

RoHS  
Compliant

SPECIFICATIONS:  
 Contact Resistance : 30mΩ max  
 Insulation Resistance : 100MΩ min. at DC 50V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

**SHOGYO INTERNATIONAL CORP.**

**# SCJ354M1N(\*)S0B00G**