



Pin Hole Layout
<Jack Bottom View>

11.	Base	PBT	1	Black Color
10.	Housing	PBT	1	Black Color
9.	Housing	PBT	1	577c Green Color
8.	Barrel	Brass	2	Nickel Plated
7.	Metal Shell B	0.2T Brass	2	Nickel Plated
6.	Metal Shell A	0.3T Iron	1	Nickel Plated
5.	Tip Spring	0.5T Brass	2	Silver Plated
4.	Break Terminal B	0.4T Brass	2	Silver Plated
3.	Break Terminal A	0.2T Phosphor Bronze	2	Silver Plated
2.	Ring Spring	0.25T Phosphor Bronze	2	Silver Plated
1.	Erath Terminal	0.2T Phosphor Bronze	2	Silver Plated
NO.	Description	Material	Q'TY	Finish

RoHS Compliant	For Reference 僅供參考
-------------------	-----------------------

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲: The Most Important Dimension

DATE	DWN	CHKD	APVD	MANAGER
10.11.2012				

PART NAME : 3.5φ PHONE JACK VERSION: 4.0

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED UNIT: mm SCALE: 1/1

SHOGYO INTERNATIONAL CORP.
#SCJ374R5NMSGB00G