



Pin Hole Layout  
(Jack Bottom View)

9.	Housing	PBT+15%G	1	Black Color
8.	Earth Terminal	0.3T Phosphor Bronze	1	Silver Plated
7.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
6.	Tip Spring	0.25T Phosphor Bronze	1	Silver Plated
5.	Tip Spring	0.25T TiCuR1-M-EH	1	Silver Plated
4.	Break Terminal	0.3T Bronze	1	Silver Plated
3.	Break Terminal	0.3T Bronze	2	Silver Plated
2.	Ring Spring	0.2T TiCuR1-M-EH	1	Silver Plated
1.	Earth Terminal	0.25T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

RoHS  
Compliant

**SPECIFICATIONS:**  
 Contact Resistance : 30mΩ max  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

		DATE	DWN	CHKD
		10.11.2012		
PART NAME : 3.5φ PHONE JACK				
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED		UNIT:mm		

**SHOGYO INTERNATIONAL CORP.**  
**# SCJ375P00(\*)S0B00G**