



11.	Barrel 3.5φ	Brass	1	Nickel Plated
10.	Barrel 2.5φ	Brass	1	Nickel Plated
9.	Housing	PBT+15%G	1	Black Color
8.	Earth Terminal	0.3T Phosphor Bronze	1	Silver Plated
7.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
6.	Tip Spring	0.25T Phosphor Bronze	1	Silver Plated
5.	Tip Spring	0.25T TiCuR1-M-EH	1	Silver Plated
4.	Break Terminal	0.3T Bronze	1	Silver Plated
3.	Break Terminal	0.3T Bronze	2	Silver Plated
2.	Ring Spring	0.2T TiCuR1-M-EH	1	Silver Plated
1.	Earth Terminal	0.25T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

RoHS
Compliant

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲: The Most Important Dimension

Pin Hole Layout
(Jack Bottom View)

DATE	DWN	CHKD
10.11.2012		

PART NAME : 3.5φ PHONE JACK	
TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED	UNIT:mm

SHOGYO INTERNATIONAL CORP.
 # SCJ375R0N(*)S0B00G