



Pin Hole Layout
<Jack Bottom View>

8	Housing	PBT+15%G	1	Black Color
7	Shunt Terminal B	0.2T Phosphor Bronze	1	Gold Plated
6	Shunt Terminal A	0.2T Phosphor Bronze	1	Gold Plated
5	Tip Spring	0.25T Brass	1	Gold Plated
4	Break Terminal B	0.25T Phosphor Bronze	1	Gold Plated
3	Break Terminal A	0.2T Phosphor Bronze	1	Gold Plated
2	Ring Spring	0.3T Phosphor Bronze	1	Gold Plated
1	Earth Terminal	0.2T Phosphor Bronze	1	Gold Plated
NO	Description	Material	Q'TY	Finish

DATE	DWN	CHKD
01.06.2012		

PART NAME : 3.5φ PHONE JACK

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm

RoHS
Compliant

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

SHOGYO INTERNATIONAL CORP.

SCJ376R7G(*)G0B00G