



Pin Hole Layout
(Jack Bottom View)

10.	Back Cover	PA9T	1	Black Color
9.	Housing	PBT+30%GF	1	Black Color
8.	Insulator	POM	2	White Color
7.	Break Terminal	0.30T Brass	1	Silver Plated
6.	Separator Terminal	0.25T Phosphor Bronze	1	Silver Plated
5.	Break Terminal	0.25T Phosphor Bronze	1	Silver Plated
4.	Separator Spring	0.3T Brass	1	Silver Plated
3.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Tip Spring	0.4T Phosphor Bronze	1	Silver Plated
1.	Earth Spring	0.25T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

DATE	DWN	CHKD
2012.08.16		

SPECIFICATIONS:

Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

RoHS Compliant For Reference 僅供參考

PART NAME : 3.5φ PHONE JACK

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm

SHOGYO INTERNATIONAL CORP.

SCJ385P00(*)S0B00G