



10	Washer	0.4T Brass	1	Nickel Plated
9	Nut	2.2T Brass	1	Nickel Plated
8	Earth Spring	0.3T Steel	1	Nickel Plated
7	Housing	PBT	1	Black Color
6	Barrel	Brass	1	Nickel Plated
5	Ring Shunt	0.4T Brass	1	Silver Plated
4	Ring Spring	0.4T Phosphor Bronze	1	Silver Plated
3	Tip Spring	0.4T Phosphor Bronze	1	Silver Plated
2	Tip Shunt	0.4T Brass	1	Silver Plated
1	Earth Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

DATE	DWN	CHKD
10.12.2011		

PART NAME : 6.3φ PHONE JACK

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm

SPECIFICATIONS:

Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: ▲: The Most Important Dimension

RoHS
Compliant

SHOGYO INTERNATIONAL CORP.
SCJ651M1N(*)S4BSWG