



8.	Washer	0.4T Brass	1	Nickel Plated
7.	Nut	2.2T Brass	1	Nickel Plated
6.	Housing	PBT	1	Black Color
5.	Ring Shunt	0.4T Brass	1	Silver Plated
4.	Ring Spring	0.4T Phosphor Bronze	1	Silver Plated
3.	Tip Spring	0.4T Phosphor Bronze	1	Silver Plated
2.	Tip Shunt	0.4T Brass	1	Silver Plated
1.	Earth Terminal	0.4T Brass	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

DATE	DWN	CHKD
10.12.2011	韓沙	李

PART NAME : 6.3 $\phi$  PHONE JACK

TOLERANCE :  $\pm 0.3$ mm UNLESS OTHERWISE SPECIFIED

UNIT: mm

RoHS Compliant

SPECIFICATIONS:  
 Contact Resistance : 30m $\Omega$  max  
 Insulation Resistance : 100M $\Omega$  min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

**SHOGYO INTERNATIONAL CORP.**  
**# SCJ651P20(\*)S4B00G**