


Arrangement of Contact



Pin Hole Layout  
(Jack Bottom View)

| 3.  | Housing     | PBT                  | 1    | Black Color    |
|-----|-------------|----------------------|------|----------------|
| 2.  | Shell       | 0.4T Brass           | 1    | Nickel Plating |
| 1.  | Terminal    | 0.2T Phosphor Bronze | 3    | Silver Plating |
| NO. | Description | Material             | Q'TY | Finish         |

RoHS  
Compliant

For Reference  
僅供參考

SPECIFICATIONS:

Contact Resistance : 30mΩ max  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstanding Voltage: AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

|  |            |     |      |      |         |
|--|------------|-----|------|------|---------|
|  | DATE       | DWN | CHKD | APVD | MANAGER |
|  | 10.19.2011 |     |      |      |         |

|   |                     |
|---|---------------------|
| PART NAME : DIN JACK                          | VERSION:4.0         |
| TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED | UNIT:mm   SCALE:1/1 |

**SHOGYO INTERNATIONAL CORP.**

**#SCN573S3NS0B000G**