



Pin Hole Layout
(Jack Bottom View)

| 6. | Spring | SWC | 1 | Nickel plated |
|-----|----------------|-------------|------|---------------|
| 5. | Insulator | PBT | 1 | Black Color |
| 4. | Insulator | PBT | 1 | Orange Color |
| 3. | Body | 0.4T Steel | 1 | Tin Plating |
| 2. | Terminal | 0.25T Brass | 1 | Tin Plating |
| 1. | Barrel(Sleeve) | 0.3T Steel | 1 | Nickel Plated |
| NO. | Description | Material | Q'TY | Finish |

| DATE | DWN | CHKD | APVD | MANAGER |
|------------|-----|------|------|---------|
| 10.18.2011 | 韩沙 | 张翠 | 张翠 | 张翠 |

PART NAME : PIN JACK

VERSION:1.0

TOLERANCE :±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm



SCALE:/

SPECIFICATIONS:
 Contact Resistance : 30mΩ max
 Insulation Resistance : 100MΩ min. at DC 500V
 Dielectric Withstanding Voltage : AC 500V for one minute
 Remark: ▲ The Most Important Dimension

RoHS
Compliant

SHOGYO INTERNATIONAL CORP.

#SCP601UNT8TT000G