



Pin Hole Layout
(Jack Bottom View)

| 9. | Washer | PBT | 1 | Yellow Color |
|-----|-------------------------|------------|------|---------------|
| 8. | Washer | PBT | 1 | Black Color |
| 7. | Washer | PBT | 1 | Red Color |
| 6. | Washer | PBT | 1 | White Color |
| 5. | Cover | ABS | 2 | Black Color |
| 4. | Base | ABS | 1 | White Color |
| 3. | Terminal T | 0.5T Brass | 2 | Silver Plated |
| 2. | Terminal D | 0.5T Brass | 2 | Silver Plated |
| 1. | Earth Terminal (Barrel) | 0.5T Brass | 2 | Nickel Plated |
| NO. | Description | Material | Q'TY | Finish |

| | | |
|------------|-----|------|
| DATE | DWN | CHKD |
| 10.04.2006 | | |

PART NAME : PIN JACK

TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED

UNIT: mm

RoHS Compliant For Reference
僅供參考

SPECIFICATIONS:
 Contact Resistance : $30\text{m}\Omega$ max
 Insulation Resistance : $100\text{M}\Omega$ min. at DC 500V
 Dielectric Withstanding Voltage AC 500V for one minute
 Remark: \blacktriangle : The Most Important Dimension

SHOGYO INTERNATIONAL CORP.

SCP6813NS321400G