



Pin Hole Layout  
(Jack Bottom View)

NO.	Description	Material	Q'TY	Finish
10.	Metal Plate	0.2T Brass	2	Nickel Plated
9.	Washer R (D)	PBT	1	Yellow Color
8.	Washer R (T)	PBT	1	Black Color
7.	Washer L (D)	PBT	1	Red Color
6.	Washer L (T)	PBT	1	White Color
5.	Cover	ABS	2	Black Color
4.	Base	ABS	1	White Color
3.	Terminal T	0.5T Brass	2	Silver Plated
2.	Terminal D	0.5T Brass	2	Silver Plated
1.	Earth Terminal (Barrel)	0.5T Brass	2	Nickel Plated

DATE	DWN	CHKD
09.06.2006		

PART NAME: PIN JACK

TOLERANCE:  $\pm 0.3\text{mm}$  UNLESS OTHERWISE SPECIFIED UNIT: mm



RoHS  
Compliant

For Reference  
僅供參考

SPECIFICATIONS:  
 Contact Resistance :  $30\text{m}\Omega$  max  
 Insulation Resistance :  $100\text{M}\Omega$  min. at DC 500V  
 Dielectric Withstanding Voltage AC 500V for one minute  
 Remark:  $\blacktriangle$ : The Most Important Dimension

**SHOGYO INTERNATIONAL CORP.**

# SCP6823NS321400G