



Pin Hole Layout  
(Jack Bottom View)

| 7.  | Washer                  | PBT        | 2    | White Color   |
|-----|-------------------------|------------|------|---------------|
| 6.  | Washer                  | PBT        | 2    | Red Color     |
| 5.  | Earth Terminal (Barrel) | 0.5T Brass | 2    | Nickel Plated |
| 4.  | Terminal D              | 0.5T Brass | 2    | Silver Plated |
| 3.  | Terminal T              | 0.5T Brass | 2    | Silver Plated |
| 2.  | Cover                   | ABS        | 2    | Black Color   |
| 1.  | Base                    | ABS        | 1    | Black Color   |
| NO. | Description             | Material   | Q'TY | Finish        |

|            |     |      |      |         |
|------------|-----|------|------|---------|
| DATE       | DWN | CHKD | APVD | MANAGER |
| 10.18.2011 | 韩沙  |      |      |         |

PART NAME : PIN JACK

VERSION:1.0

TOLERANCE : $\pm 0.3$ mm UNLESS OTHERWISE SPECIFIED

UNIT:mm



SCALE: /

SPECIFICATIONS:

Contact Resistance : 30m $\Omega$  max  
 Insulation Resistance : 100M $\Omega$  min. at DC 500V  
 Dielectric Withstand Voltage : AC 500V for one minute  
 Remark:  $\Delta$ : The Most Important Dimension

RoHS  
Compliant

**SHOGYO INTERNATIONAL CORP.**

**#SCP6831NS3232T1G**