



Pin Hole Layout
Jack Bottom View

10.	Matal Plate	0.2T Brass	2	Nickel Plated
9.	Washer	PBT	1	Red Color
8.	Washer	PBT	1	White Color
7.	Washer	PBT	1	Red Color
6.	Washer	PBT	1	White Color
5.	Cover	ABS	2	Black Color
4.	Base	ABS	1	White Color
3.	Terminal T	0.5T Brass	2	Silver Plated
2.	Terminal D	0.5T Brass	2	Sliver Plated
1.	Earth Terminal (Barrel)	0.5T Brass	2	Nickel Plated
NO.	Description	Material	Q'TY	Finish

DATE	DWN	CHKD
12.20.2005		

PART NAME : PIN JACK

TOLERANCE : $\pm 0.3\text{mm}$ UNLESS OTHERWISE SPECIFIED

UNIT: mm

RoHS Compliant For Reference 僅供參考

SPECIFICATIONS:
 Contact Resistance : $30\text{m}\Omega$ max
 Insulation Resistance : $100\text{M}\Omega$ min. at DC 500V
 Dielectric Withstand Voltage : AC 500V for one minute
 Remark: ▲ : The Most Important Dimension

SHOGYO INTERNATIONAL CORP.

SCP6863NS323200G