



仕様 SPECIFICATION	
1. 定格: MJ-084N=DC13.5V 2A RATING (EIAJ RC5320A TYPE4 電圧区分4)	MJ-085N=DC18V 2A (EIAJ RC5320A TYPE5 電圧区分5)
2. 絶縁抵抗: DC500V/100MΩ以上 INSULATION RESISTANCE: 100MΩMIN/500V DC.	
3. 耐電圧: AC500V 1分間。 BREAKDOWN VOLTAGE: 500V AC FOR 1MINUTE.	

MODLE	A	B	C
MJ-085N	φ7	φ4	φ1.45
MJ-084N	φ5.9	φ3	φ1.05

TOLERANCE	SCALE	DATE	DESING	DRAW	INSPE	APRO
±0.5	2/1	07/2/25	K.S	K.S	N.I	M.K

LET	PART NAME	MATERIAL	QTY	FINISH
6	CAP	キャップ	PE	1
5	SLEEVE LUG	スリーブ ラグ	BSR t=0.3	1 Ni
4	CENTER CONTACT	コンタクト	PBS t=0.5	1 Sn
3	SLEEVE SPRING	スリーブ*バネ	PBS t=0.25	2 Sn
2	BUSHING	スリーブ*メタル	BSBM	1 Ni
1	HOUSING	ケース	PA	1

MODEL 型式	QTY	PART NAME 品名	DC INLINE JACK (TYPE 4 / 5) No. MJ-084N/MJ-085N
MATERIAL 材質		DRAW. NO 図番	MJ085N
FINISH 処理	SHOGYO INTERNATIONAL CORPORATION		