



Dielectric Strength: AC 500V for one minute
 Insulation Resistance: 100MΩ min. at DC 500V
 Contact Resistance: 50mΩmax.

| | | | | |
|----|--------------|-----|----------|--------|
| 8 | CAP | 1 | P. E | |
| 7 | TERMINAL B | 1 | ST | NI |
| 6 | TERMINAL A | 1 | ST | NI |
| 5 | INSURATOR C | 1 | P. F | |
| 4 | SLEEVE METAL | 1 | BSBM | NI |
| 3 | INSURATOR B | 1 | P. V. C | |
| 2 | INSULATOR A | 1 | EVONITE | |
| 1 | TIP PIN | 1 | BSBM | NI |
| No | PART NAME | QTY | MATERIAL | FINISH |

| | | | | | | |
|----------------|-------|----------------------------------|-----------------|------|-----------|------|
| TOLERANCE | SCALE | DATE | DESING | DRAW | INSPE | APRO |
| ±0.3 | 2/1 | | | N. I | | |
| MODEL 型式 | | QTY | PART NAME 品名 | | MP-105AC | |
| MATERIAL 材質 | | | DRAW. NO 図番 | | MP105AC-E | |
| FINISH 処理 | | SHOGYO INTERNATIONAL CORPORATION | | | | |