



- ① Series No.
- ② Center Pin Diameter: “A”: Ø1.3mm, “B”: Ø1.65mm, “C”: Ø2.0mm, “D”: Ø2.5mm, “E”: Ø1.0mm, “F”: Ø0.65mm, “G”: Ø2.95mm, “J”: Ø1.5mm (For SCD461/463), “L”: Ø1.87mm

*The available center pin options for each Series are listed in our product offerings on the site. If the Pin diameter that you require is not listed, then it is not standardly available.

- ③ Schematic Code: “C”: Normally Closed, “P”: Normally Open, “L”: Normally Independent (For SCD412 Only).
- ④ Terminal Plating: “S”: Silver (Standard), “T”: Tin, “M”: Misty Silver, “N”: Nickel
- ⑤ Special Option: “000”: No Special Option
 - (i) For SCD415/420/452/457/458:
 - “001”: Flat PC Pins
 - “003”: Kinked PC Pins
 - “005”: Kinked, Fork Type, PC Pins
 - (ii) For SCD454/554:
 - “001”: Without Threaded Bushing
 - “003”: With Threaded Bushing, but without Nut
 - “103”: With Threaded Bushing and Nut
 - (iii) For SCD438/441/442/443:
 - “011”: With Flat PC Pins and Without Groove in Housing
 - “013”: With Kinked PC Pins and Without Groove in Housing
 - “031”: With Flat PC Pins and Groove in Housing
 - “033”: With Kinked PC Pins and Groove in Housing
 - (iv) For SCD456/556:
 - “011”: With Flat PC Pins and Unthreaded Bushing
 - “031”: With Kinked PC Pins and Unthreaded Bushing
 - “113”: With Flat PC Pins, Threaded Bushing, and Nut
 - “133”: With Kinked PC Pins, Threaded Bushing, and Nut
- ⑥ Plastic Housing Color: “B”: Black (Standard), “A”: Gray, “G”: Green, “I”: Beige, “R”: Red, “O”: Orange, “P”: Pink, “U”: Blue, “W”: White
- ⑦ Reserved for special options. Otherwise “00”
- ⑧ RoHS Compliance: “G”