



- ① Series Number (For SCP663/664/665/671/672/675/681/682/683/684/685/686/687/688/691/692/695/696/697/698)
- ② Plastic Housing Color: “1”: Black, “2”: Red, “3”: White, “4”: Yellow, “5”: Blue, “6”: Gray, (For SCP672, this spot is for the schematic code. See PDF drawing on individual part pages for available option(s))
- ③ Bushing Plating: “N”: Nickel (Standard), “G”: Gold Flash
- ④ Terminal Plating: “T”: Tin, “S”: Silver, “G”: Gold Flash
- ⑤ Insulator Color Code Arrangement (From Left -> Right/Top -> Bottom/Top Left ->Bottom Left->Top Center->Bottom Center, etc.): “1”: Black, “2”: Red, “3”: White, “4”: Yellow, “5”: Blue, “6”: Gray, “7”: Green, “8”: Orange, “9”: Brown. Fill in the remaining spaces with “0”. For example, a 2-Port Connector could be “3 4 0 0 0 0”. Exceptions are below.
  - (i) For SCP675, format is \_\_\_ N 0 0
  - (ii) For SCP683T1/687T1/SCP688T1 Series, format is \_\_\_ I 1
  - (iii) For SCP687T2/SCP688T2 Series, format is \_\_\_ I 2
- ⑥ RoHS Compliance: “G”