

PCB LAYOUT

NOTES:

0.25mm PHOSPHOR BRONZE 1/2H, NICKEL PLATED 4"~6u"

TEMPERATURE RANGE: -40°C TO +270°C

*VIBRATION TEST: 10-50-10 HZ SWEEPED IN 60 SECONDS

X, Y, Z DIRECTION: 1 HOUR EACH DIRECTION

*RESULT: NO DISLODGE-
MENT OF THE CELL OR DAMAGE

NO DISCONTINUITY OVER 10 MICRO-SECONDS

*SHOCK TEST: HALF SINE WAVE ACCELERATION 150G, 6 MILLI-SECONDS


3 SHOCK PULSES EACH DIRECTION PER AXIS, TOTAL OF 18 PULSES

*RESULT: NO EVIDENCE OF PHYSICAL DAMAGE

*DROP TEST: DROPPED FROM 1M HIGH TO CONCRETE FLOOR

*RESULT: NO EVIDENCE OF PHYSICAL DAMAGE

ROHS 2 COMPLIANT

3				
2				
1	原规格ML414改为: BC-4801	NOV/27/2015		
NO.	MODIFICATION	DATE	SCALE	1:1
General Tolerances			UNIT	MM
0.	±0.5	 The Third Angle Projection	MATERIAL	C5191 1/2H
0.X	±0.1		DATE	SEP. 04. 2015
0.XX	±0.05		Angle: ±2°	

SHOGYO INTERNATIONAL CORP.

#BC-4801

BATTERY CLIP