



CONTACT & WIRE ASSEMBLY

1. ANODE CONTACT & WIRE COMBINATION
MATERIAL: BRASS NICKEL PLATED




2. CATHODE CONTACT & WIRE COMBINATION
MATERIAL: PHOSPHOR BRONZE NICKEL PLATED



SPECIFICATION

- (1) ITEM NO. : BHC-511A150MM
- (2) WIRE: UL1007 AWG #26
BLACK & RED: 150MM±5MM
STRIP & TIN: 5MM±1MM
- (3) HOLDER MATERIAL: PP UL94HB RESIN, BLACK COLOR
- (4) CONTACT MATERIAL:
ANODE: 0.25MM THICK BRASS NICKEL PLATED
CATHODE: 0.25MM THICK PHOSPHOR BRONZE NICKEL PLATED
- (5) RoHS COMPLIANT

3				
2				
1				
NO.	MODIFICATION	DATE	SCALE	1.5:1
General Tolerances			UNIT	MM
0 ~ >3	± 0.10	30 ~ >120	± 0.30	 The Third Angle Projection
3 ~ >6	± 0.10	120 ~ >400	± 0.50	
6 ~ >30	± 0.20	Angle: ± 3°		
			MAT'L	SEE SPEC.
			DATE	NOV. 10, 2014

SHOGYO INTERNATIONAL CORP.

#BHC-511A150MM

BATTERY HOLDER