



CONTACT & WIRE ASSEMBLY


1. ANODE CONTACT & WIRE COMBINATION
MATERIAL: BRASS NICKEL PLATED



2. CATHODE CONTACT & WIRE COMBINATION
MATERIAL: PHOSPHOR BRONZE NICKEL PLATED




3. CATHODE ANODE: SPRING STEEL NICKEL PLATED



SPECIFICATION

- (1) ITEM NO. : BHC-521A150MM
- (2) WIRE: UL1007 AWG #26
BLACK & RED: 150MM±5MM
STRIP & TIN: 5MM±1MM
- (3) HOLDER MATERIAL: PP UL94HB RESIN, BLACK COLOR
- (4) CONTACT MATERIAL:
ANODE: 0.25MM THICK BRASS NICKEL PLATED
CATHODE: 0.25MM THICK PHOSPHOR BRONZE NICKEL PLATED
CATHODE ANODE: 0.20MM THICK SPRING STEEL NICKEL PLATED
- (5) RoHS COMPLIANT

3					
2					
1					
NO.	MODIFICATION	DATE	SCALE	1.5:1	
General Tolerances			UNIT	MM	
0 ~ >3	± 0.10	30 ~ >120 ± 0.30	 The Third Angle Projection	MAT'L	SEE SPEC.
3 ~ >6	± 0.10	120 ~ >400 ± 0.50		DATE	NOV. 10. 2014
6 ~ >30	± 0.20	Angle: ± 3°			

SHOGYO INTERNATIONAL CORP.
#BHC-521A150MM
 BATTERY HOLDER