


SPECIFICATION

- (1) ITEM NO. : BH-431-2A
- (2) WIRE: UL1007 AWG#26  
BLACK & RED:  $150\text{MM} \pm 5\text{MM}$   
STRIP & TIN:  $5\text{MM} \pm 1\text{MM}$
- (3) HOLDER MATERIAL: PP RESIN, BLACK COLOR
- (4) SPRING MATERIAL:  $\text{Ø}0.64$  MM SPRING STEEL NICKEL PLATED
- (5) RIVET MATERIAL: BRASS NICKEL PLATED
- (6) RoHS COMPLIANT

3					
2					
1			NAME	BATTERY HOLDER: BH-431-2A	
NO.	MODIFICATION	DATE	SCALE	1:1	APPD <i>[Signature]</i>
General Tolerances			UNIT	MM	CHKD <i>[Signature]</i>
0 ~ >3	$\pm 0.10$	30 ~ >120	$\pm 0.30$	MAT'L	SEE SPEC. DWN Rao xianhui
3 ~ >6	$\pm 0.10$	120 ~ >400	$\pm 0.50$	DATE	FEB. 02. 2018 DR NO 4312A-0218A
6 ~ >30	$\pm 0.20$	Angle: $\pm 3^\circ$	 The Third Angle Projection		

**SHOGYO INTERNATIONAL CORP.**  
**BH-431-2A**  
**BATTERY HOLDER**