



NOTES

- (1) PART NO. : 223-2A ANODE
- (2) MATERIAL: 0.4MM STEEL NICKEL PLATED
- (3) SPRING MATERIAL: Ø0.5MM SPRING STEEL NICKEL PLATED
- (4) TOLERANCE: ISO 2768-M, UNLESS OTHERWISE SPECIFIED
- (5) PROCESS CORNER R=0.40MM
- (6) SURFACE NO BURRS, NO GREASE
- (7) RoHS COMPLIANT

△	Change the material to steel	Apr/29/2019
△	Change the size from 2.0 to 2.2mm from 0.3 to 0.4mm	Oct/24/2018
△	Change the size from 6.0 to 5.0mm from 0.8 to 1.0mm Add the size 0.3mm	JUL/23/2018

NO.	MODIFICATION	DATE
General Tolerances		
0 - >3	± 0.10	30 - >120 ± 0.50
3 - >6	± 0.20	120 - >400 ± 0.80
6 - >30	± 0.30	Angle: ± 3°



NAME	BATTERY CONTACT: 223-2A ANODE		
SCALE	4:1	APPD	<i>[Signature]</i>
UNIT	MM	CHKD	<i>[Signature]</i>
MAT'L	SEE NOTES	DWN	Rao xianhui
DATE	APR. 29. 2019	DR NO	D2-2232A-0419

**SHOGYO INTERNATIONAL CORP.**  
**223-2A ANODE**  
 BATTERY CONTACT