



△	Add the convex	Nov/10/2018
⑥	Change the size from 0.5 to 0.3mm from 0.3 to 0.4mm	Oct/24/2018
⑤	Change the size from 11.0 to 6.9mm	Aug/14/2018
④	Change the size from 6.0 to 5.0mm from 0.8 to 1.0mm Add the size 0.3mm	JUL/23/2018
③	Change these size: from 1.2 to 1.5mm	Jun/11/2018
②	Change these size: from 4.25 to 3.5mm from 9.7 to 10.4mm	Jun/11/2018
①	Change these size: from 5.0 to 4.25mm from 18.0 to 18.7mm	May/30/2018

NO.	MODIFICATION	DATE
General Tolerances		
0 ~ >3	± 0.10   30 ~ >120 ± 0.30	 The Third Angle Projection
3 ~ >6	± 0.10   120 ~ >400 ± 0.50	
6 ~ >30	± 0.20   Angle: ± 3°	

NAME	BATTERY CONTACT: 223-2C ANODE CATHODE		
SCALE	4:1	APPD	<i>[Signature]</i>
UNIT	MM	CHKD	<i>[Signature]</i>
MAT'L	SEE NOTES	DWN	Rao xianhui
DATE	NOV. 10. 2018	DR NO	D2-2232C-1118 <small>REV II</small>

NOTES

- (1) PART NO. : 223-2C ANODE CATHODE
- (2) MATERIAL: 0.40MM THICK STEEL NICKEL PLATED
- (3) SPRING MATERIAL: Ø0.5MM SPRING STEEL NICKEL PLATED
- (4) TOLERANCE: ISO 2768-M, UNLESS OTHERWISE SPECIFIED
- (5) PROCESS CORNER R=0.40MM
- (6) SURFACE NO BURRS, NO GREASE
- (7) RoHS COMPLIANT

**SHOGYO INTERNATIONAL CORP.**  
**223-2C ANODE CATHODE**  
 BATTERY CONTACT