



SPECIFICATIONS:

- (1) ITEM NO: BH-411-2A
- (2) WIRE: UL1007 AWG #26
BLACK & RED: 150MM ± 5MM
STRIP & TIN: 5MM ± 1MM
- (3) HOLDER MATERIAL: PP 94HB RESIN, BLACK COLOR
- (4) SPRING MATERIAL: Ø0.6MM SPRING STEEL NICKEL PLATED
- (5) RIVET MATERIAL: BRASS NICKEL PLATED
- (6) RoHS COMPLIANT

△2	Changed wire output holes from round to square	Aug/30/12	SHOGYO INTERNATIONAL CORP.			
△1	Changed dimension from 45.20 to 46.50	Aug/21/07				
NO.	MODIFICATION	DATE	NAME	BATTERY HOLDER: BH-411-2A		
General Tolerances			SCALE	1.5:1	APPD	<i>[Signature]</i>
0 ~ >3	± 0.10	30 ~ >120 ± 0.30	UNIT	MM	CHKD	<i>[Signature]</i>
3 ~ >6	± 0.10	120 ~ >400 ± 0.50	MAT'L	SEE SPEC.	DWN	<i>[Signature]</i>
6 ~ >30	± 0.20	Angle: ± 3°	DATE	JUN. 08. 2003	DR NO	4112A-0703

