







改訂(Rev.)	改訂(Revision)	年月日(Date)	図面(Drawn)	承認(Approved)
△				
△				

特記事項(Special remarks)

- 性能は、取扱説明書による。
The performance should follow the standards specified in the appended sheets.
- 本製品のプラグは、#3.5 3極ミニ型同心プラグとす。
(JIS C8560規格に準ずる。)
Using plug is #3.5 3-pole mini size concentric plug (Drawing No.EMJ-00138) .
Provided that they conform to JIS C8560.
- 公差未指定は、±0.2mmとする。
Unspecified tolerance of dimension shall be ±0.2mm.
- 本製品の製造工程において(鉛、六価クロム、フロン、有機溶剤、Pb、Cd、Hg、Cr(VI)、PCB等)は使用していません。
No ozone depleting substances are used in the manufacturing process of this product.
- プラグ挿入時端子(2)と(3)、(1)と(3)のプラグチップを挟んでショート、漏れ等の問題とす。
Short-circuited on the terminal with plug-tip of inserting the plug is not assumed to be a problem.



回路図 (Circuit)

t1.0 プリント基板参考図 (公差±0.1mm, 銅箔面側より見る)
t1.0 P.W.B. (Tolerance ±0.1mm)
(Seen from copper leaf side.)

4	Body	1	PA66	Black	UL94HB
3	Resilient terminal R	1	C5191R	As plated 1um or more	t0.25
2	Resilient terminal L	1	C5210R	As plated 1um or more	t0.3
1	Ground terminal	1	C5191R	As plated 1um or more	t0.25
No.	品名 (Name of part)	数量 (Qty)	材質 (Material)	仕様 (Specification)	
備考 (Remarks)					
承認 Approved	確認 Checked	設計 Designed	A3K	スケール Scale	2:1
			図面 Date	Mar. 4, 2005	R.D.

SHOGYO INTERNATIONAL CORP.
#M03-681A0