



10.	Insulator	POM	1	White Color
9.	Cover	POM	1	White Color
8.	Housing	PBT	1	Black Color
7.	Separator Spring	0.2T Phosphor Bronze	1	Silver Plated
6.	Break Terminal	0.3T Brass	1	Silver Plated
5.	Separator Spring	0.2T Phosphor Bronze	1	Silver Plated
4.	Break Terminal	0.3T Brass	1	Silver Plated
3.	Ring Spring	0.25T Phosphor Bronze	1	Silver Plated
2.	Chip/Tip Spring	0.3T Phosphor Bronze	1	Silver Plated
1.	Earth Terminal	0.25T Phosphor Bronze	1	Silver Plated
NO.	Description	Material	Q'TY	Finish

DATE	DWN	CHKD
01.10.2012		

PART NAME : 3.5 \varnothing PHONE JACK

TOLERANCE : ± 0.3 mm UNLESS OTHERWISE SPECIFIED

UNIT: mm

SPECIFICATIONS:

Contact Resistance : 30m Ω max
 Insulation Resistance : 100M Ω min. at DC 500V
 Dielectric Withstanding Voltage: AC 500V for one minute
 Remark: \blacktriangle : The Most Important Dimension

RoHS
Compliant

SHOGYO INTERNATIONAL CORP.

SCJ344P00(*)S0B00G