


19.	Break Terminal(DOWN)	0.4T Bronze	1	Silver Plated
18.	Ring Spring(DOWN)	0.3T Phosphor Copper	1	Silver Plated
17.	Back Housing Cover	ABS	1	Transparent
16.	Back Housing	PBT	1	Black Color
15.	Switch Pin	0.4T Brass	6	Silver Plated
14.	Bushing(TOP)	PBT	1	577C Green Color
13.	Bushing(DOWN)	PBT	1	284C Blue Color
12.	Sleeve(Barrel)	Brass	1	Nickel Plated
11.	Metal Shell	0.2T Phosphor Copper	1	Silver Plated
10.	Cover	PBT	1	Black Color
9.	Housing	PBT	1	Black Color
8.	Tip Lead(TOP)	0.4T Brass	1	Silver Plated
7.	Tip Spring(TOP)	0.25T Phosphor Copper	1	Silver Plated
6.	Ring Lead(TOP)	0.4T Brass	1	Silver Plated
5.	Ring Spring(TOP)	0.25T Phosphor Copper	1	Silver Plated
4.	Earth Terminal(TOP)	0.4T Phosphor Copper	1	Silver Plated
3.	Tip Spring(DOWN)	0.25T Phosphor Copper	1	Silver Plated
2.	Ring Spring(DOWN)	0.3T Phosphor Copper	1	Silver Plated
1.	Earth Terminal(DOWN)	0.4T Phosphor Copper	1	Silver Plated
NO.	Description	Material	Q'TY	Finish



Pin Hole Layout
(Jack Bottom View)

RoHS
Compliant

SPECIFICATIONS:
Contact Resistance : 30mΩ max
Insulation Resistance : 100MΩ min. at DC 500V
Dielectric Withstand Voltage : AC 500V for one minute
Remark: ▲ : The Most Important Dimension

SHOGYO INTERNATIONAL CORP.

SCJ352M5N(*)SGUN4G

PART NAME : 3.5φ PHONE JACK

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm

