



10.	Nut	2.2T Brass	1	Nickel Plated
9.	Washer	0.4T Brass	1	Nickel Plated
8.	Earth Spring	0.3T Steel	1	Nickel Plated
7.	Tip Shunt	0.4T Bronze	1	Silver Plated
6.	Tip Spring	0.4T Phosphor Bronze	1	Silver Plated
5.	Ring Shunt	0.4T Bronze	1	Silver Plated
4.	Ring Spring	0.4T Phosphor Bronze	1	Silver Plated
3.	Sleeve Shunt	0.4T Bronze	1	Silver Plated
2.	Barrel	Brass	1	Nickel Plated
1.	Housing	PA66	1	Black Color
NO.	Description	Material	Q'TY	Finish

DATE	DWN	CHKD
10.12.2011		

SPECIFICATIONS:  
 Contact Resistance : 30mΩ max  
 Insulation Resistance : 100MΩ min. at DC 500V  
 Dielectric Withstand Voltage : AC 500V for one minute  
 Remark: ▲: The Most Important Dimension

RoHS  
Pb Free Process

PART NAME : 6.3φ PHONE JACK

TOLERANCE : ±0.3mm UNLESS OTHERWISE SPECIFIED

UNIT:mm

**SHOGYO INTERNATIONAL CORP.**

# SCJ635MIN(\*)S4BP0G