




SHOGYO INTERNATIONAL CORP.

www.shogyo.com

SPEAKER SPECIFICATIONS

MODEL NO.	GF1260X-1 (RoHS)				
1	NOMINAL SIZE	77.5 x 125.6 mm	3 x 5	inch	
2	IMPEDANCE	8 $\Omega \pm 15\%$	at. 800 Hz	1 V	
3	RESONANCE FO	175 Hz ± 35 Hz	FO Hz	1 V	
4	S.P. LEVEL	96 dB/w ± 3 dB	1 W	50 cm average at	
5	FREQ. RESPONSE	Fo Hz $\sim 20K$ Hz	MAX 10 dB	600, 800, 1K, 1.2K Hz	
6	INPUT POWER	Nominal Input 6 W	Handling Capacity 10 W		
7	OPERATION	Must be normal at program source 6 W			
8	BUZZ, RATTLE, ETC.	Must be normal at Sine Wave 6.9 V			
9	MAGNET	60 x 32 x 8 mm			
10	FLUX DENSITY	Gauss $\pm 10\%$	total flux max well within		
11	TOTAL WEIGHT	gr	oz		
12	LOAD TEST	After test meets Item 7 and 8	White noise 6 W	24 Hours	
13	DISTORTION				
14	HEAT TEST	After test meets Item 7 and 8	70 $\pm 2^\circ$ C	20-50 % R.H. 24 Hours	
15	HUMIDITY TEST	After test meet Item 7 and 8	40 $\pm 2^\circ$ C	90-95 % R.H. 24 Hours	





TOLERANCE: ± 0.8 MM

MODEL NO. GF1260X-1

APPROVED	CHECKED	DRAWING

SHOGYO INTERNATIONAL CORP.